RF COAXIAL TERMINATION

1.85 mm Male RF Terminator

DC–67 GHz | 50 Ω | 2 W

P/N VST-F-185M0201-67G

PRODUCT OVERVIEW

A fixed 50 Ω coaxial terminator with a 1.85 mm male interface, specified for DC–67 GHz operation and 2 W rated power.



KEY FEATURES

- DC–67 GHz frequency coverage
- 2 W rated power
- 1.85 mm male coaxial interface
- Passivated stainless-steel housing

APPLICATIONS

- Termination of unused RF/mmWave ports
- RF component and interconnect testing
- Broadband coaxial measurement fixtures

ELECTRICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
Frequency Range	**DC–67 GHz**
Nominal Impedance	**50 Ω**
VSWR (Max.)	**≤1.25:1 (DC–67 GHz)**
Rated Power	**2 W**
Temperature Range	**–55 °C to +125 °C**
Connector Interface	**1.85 mm Male**


RF COAXIAL TERMINATION

Mechanical & Material Details

1.85 mm Male RF Terminator / VST-F-185M0201-67G

MECHANICAL OUTLINE

Dimensions in mm



MECHANICAL DATA	SPECIFICATION
Overall Length	**18.1 mm**
Body Diameter	**Ø7 mm**
Thread Callout	**M7×0.75-6H**
Connector Interface	**1.85 mm Male**

MATERIALS & FINISH	SPECIFICATION
Body	**Stainless steel, passivated**
Internal Contact	**Beryllium copper, gold plated**
Outer Conductor	**Stainless steel, passivated**
Insulator	**PEEK**

ORDERING INFORMATION VST-F-185M0201-67G

1.85 mm Male RF Terminator