RF COAXIAL TERMINATION

2.4 mm Female RF Terminator

DC–50 GHz | 50 Ω | 2 W

P/N VST-F-24F0201-50G

PRODUCT OVERVIEW

A fixed 50 Ω coaxial termination with a 2.4 mm female interface, specified for operation from DC to 50 GHz.



KEY FEATURES

- VSWR ≤1.20:1 to 40 GHz and ≤1.25:1 to 50 GHz
- 2 W rated power in a compact 13 mm design
- Passivated stainless-steel construction with gold-plated brass RF contact

APPLICATIONS

- Termination of unused RF/mmWave ports
- RF component and interconnect testing
- Broadband coaxial measurement fixtures

ELECTRICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
Frequency Range	**DC–50 GHz**
Nominal Impedance	**50 Ω**
VSWR (DC–40 GHz)	**≤1.20:1**
VSWR (DC–50 GHz)	**≤1.25:1**
Rated Power	**2 W**
Temperature Range	**−55 °C to +125 °C**
Connector Interface	**2.4 mm Female**


RF COAXIAL TERMINATION

Mechanical & Material Details

2.4 mm Female RF Terminator / VST-F-24F0201-50G

MECHANICAL OUTLINE

Dimensions in mm



MECHANICAL DATA	SPECIFICATION
Overall Length	**13 mm**
Wrench Flats	**8 mm**

MATERIALS & FINISH	SPECIFICATION
Body	**Stainless steel, passivated**
Internal Contact	**Brass, gold plated**
Outer Conductor	**Stainless steel, passivated**
Insulator	**PEI**

ORDERING INFORMATION VST-F-24F0201-50G

2.4 mm Female RF Terminator